

QC Kit IBAcan



Complete measuring kit for luminance measurements at image display devices (black/white) according to DIN V 6868-57 (acceptance tests) and IEC 61223-2-5 (constancy tests), AAPM TG18.

Iba

Consisting of:

Spot-Luminance-Meter LXcan **VD0601400**

incl. mask for screen contact measurements.

Power supply **VD0601410**

with 4 adapters (RoHS conform) - USB-cable is absolutely necessary

USB cable * **VD0601450**

for automatic transfer of the measured data and for recharging batteries

Carrying case **VD0225905**

***Alternatively to USB-cable, but exclusively for automatic transfer of the measured data:**

Interface cable **VD0601460**

(2 m) RS 232 for automatic transfer of the measured data

Optional accessories:

Illuminance detector LX-LS **VD0602960**

for measuring illuminance (lux) in the ambient light of image display devices and at viewing boxes.

Tripod **VD0610200**

for measuring device LXcan, adjustable height 60 cm – 153 cm.

High precision mini tripod **VD0610210**

for measuring device LXcan, adjustable height 24.5 cm – 36.5 cm.

(The Tripod cannot be put into the carrying case!)

Manufacturer:

Germany
IBA Dosimetry GmbH
Bahnhofstr. 5
90592 Schwarzenbruck
Tel.: +49 9128 607 0
Fax: +49 9128 607 10

USA
IBA Dosimetry America
3150 Stage Post Drive, Suite 110
Bartlett, TN 38133
Tel.: +1 901 386 2242
Fax: +1 901 382 9453

Sweden
IBA Dosimetry AB
P.O. Box 1004
751 40 Uppsala
Tel.: +46 18 18 07 00
Fax: +46 18 12 75 52

China
IBA Dosimetry China
No.6, Xing Guang Er Jie Beijing
OPTO-mechatronics
Industrial Park (OIP),
Tongzhou District
Beijing 101111
Tel.: +86 10 8080 9288
Fax: +86 10 8080 9299

The Philosophy of **Precision & Simplicity**

Note:

Depicted Pictures and images may differ from the actual scope of delivery.
Technical data is subject to change without prior notice.

Protect,
enhance
and save
lives

iba